

Specifications

型號 MODEL	WA-460HA	WA-530HA
鋸切能力 Capacity	● 460 mm ■ 480 x 460 mm	● 530 mm ■ 530 x 530 mm
鋸切尺寸 Blade Size	41 x 1.3 x 5450 mm	41 x 1.3 x 5980 mm
鋸帶速度 Blade Speed	(50 Hz) 16.7 x 70.8 mpm / (60 Hz) 20 x 85 mpm	(60 Hz) 20 ~ 100 mpm
鋸帶馬達 Blade Motor	7.5 HP (5.7 kw) 4P	7.5 HP (5.5 kw)
油壓馬達 Hydraulic Motor	2 HP (1.5 kw) 4P	2 HP (1.5 kw)
冷卻馬達 Coolant Motor	1/4 HP (0.18 kw)	1/4 HP (0.2 kw)
油壓油箱 Hydraulic Tank	88 Liters	100 Liters
冷卻水箱 Coolant Tank	117 Liters	110 Liters
台面高度 Table Height	810 mm	800 mm
送料行程 Feeding Stroke	510 mm	500 mm
殘料長度 Minimum Residual Work Length	85 mm	85 mm
束材切割 Bundle Cutting (W x H)	210 ~ 130 mm x 360 ~ 230 mm	230 ~ 400 mm x 120 ~ 270 mm
最小鋸切尺寸 Mini. Cut Off Length	Over 8 mm	Over 8 mm
最小無料檢知尺寸 Mini. No Material Detecting	25 mm	25 mm
裝箱尺寸 Packing Size (W x L x H)	2870 x 2300 x 2200 mm	3000 x 2150 x 2200 mm
淨重/毛重 N.W / G.W	2800 kgs / 3280 kgs	3800 kgs / 4280 kgs



油壓控制式鎢鋼導塊導正鋸帶
鎢鋼導塊用油壓夾持方式，快速、穩定及方便操作。

TUNGSTEN CARBIDE GUIDED BLADE BY HYDRAULIC CONTROL
Using hydraulic to set tungsten carbide to guide the blade that is easy to operate and get stable function.



油壓鋸帶張力自動控制裝置
鋸帶張力調整使用油壓缸驅動方式，快速、準確及省力。

HYDRAULIC BLADE TENSION DEVICE
Blade tension device for easy blade tension setting, it is both quick and precise.

**NC人機觸控面板**

控制面板採圖示及觸控式設計，操作方便、故障自動顯示及鋸切尺寸可做多段性之設定與記憶。

NC TOUCH SCREEN AND CONTROL PANEL

Control panel and touch screen are very easy to read and operate, this has multiple functions for setting and programming with an indicator to show abnormal functioning device.



林寶機械貿易私人有限公司

LIM POH MACHINERY TRADING PTE LTD

NO. 111, UBI AVE 4, CIVIC TERRACE WAREHOUSE, SINGAPORE 408761.

E-mail: enquiry@limpoh.com Website: http://www.limpoh.com

TEL: 6846 1138 FAX: 6841 2832

GST Reg. No. M2-0067812-5 Business Reg. No. 198404054E