

● Mechanical Specification:

MODEL	UNIT	SHM-1200	SHM-1400	SHM-1800	SBM-1960
Table					
Table Size	mm	1100x800		1500x800	
T-Slots	mm	20x7			
Maximum Loading	kg	1200		2000	
Height From Ground	mm	850		950	
Travel					
X Axis Travel	mm	1200	1400	1800	
Y Axis Travel	mm	1200(1400)		1400(1700)	1960
Z Axis Travel	mm	800(1000)		1200(1400)	
Distance					
Distance Between Spindle Center to Working Table	mm	0-1200(0-1400)		0-1400(0-1700)	
Spindle					
Spindle Taper		- NT#50(BT#50)			
Spindle Changing Speed	rpm	45-1500(30-1000)			
X.Y.Z Axis 12 Steps Cutting Speed(60/50 HZ)	mm/min	28-875 / 23-730			
Z axis 12 Steps Boring Speed (60/50 HZ)	mm/rev.	0.028-0.875 / 0.023-0.73			
X.Y.Z Axis Rapid Speed (60/50 HZ)	mm/min	2800 / 2400			
Motor					
Main Motor	kw	5.5x4P(6P) / 7.5x4P(6P)			
Spindle Cycle Lubrication Motor	kw	0.2x4P			
Centralized Lubrication Motor	w	25			
Auto Feed Gear Box Motor	kw	0.75x4P		1.2x4P	
Cutting Coolant Motor	kw	0.1x4P			
Transmission Motor	kw	1.5x4P			
Machine Dimension					
Machine Weight	kg	6500	6800	10000	10500
Floor Space Requirement	mm	3200x3600	3400x3600	4300x4400	4500x4400

★ () As Optional



CNC Double Column Machining Center Series
SDM-1714(L) / 7235(L)



CNC Bed's Universal Milling Machining Series
SBM-2000L / 2600L / 3000L / 3500L



CNC Vertical Machining Centers
SVM-1100 / 1500L



林寶機械貿易私人有限公司

LIM POH MACHINERY TRADING PTE LTD

NO. 111, UBI AVE 4, CIVIC TERRACE WAREHOUSE, SINGAPORE 408761.

E-mail: enquiry@limpoh.com Website: http://www.limpoh.com

TEL: 6846 1138 FAX: 6841 2832

GST Reg. No. M2-0067812-5 Business Reg. No. 198404054E