

## 規格 Specification

Item		CRT-18/20B	CRT-20/25B
工作台尺寸 Table size	Ⓐ×Ⓑmm (in)	1,800×2,000 (70×78)	2,000×2,500 (78×98)
工作台最大迴轉直徑 Table rotating maximum dia	ψⒸmm (in)	2,565 (101)	2,970 (117)
滑動行程 Saddle traverse (Zaxis)	Ⓢmm (in)	1,000 (39)	1,500 (59)
工作台最大承載重量 Maximum load on table	Kg (lb)	12,000 (26,400)	20,000 (44,000)
工作台旋轉速度 Rapid rotation of table	min-1(rpm)	0.8	0.8
滑動切削進給 Saddle cutting feed	mm/min (in/min)	1~3,000 (0.04~118)	1~3,000 (0.04~118)
滑動行程速度 Saddle rapid traverse	mm/min (in/min)	6,000 (236)	6,000 (236)
最大推力 Max. thrust	N (kgf/lbf)	19,600 (2,000/4,410)	29,400 (3,000/6,615)
電容量 Electric power source capacity	KVA	14	14
機械尺寸 Machine size	Ⓓ×Ⓔ×Ⓕmm (in)	3,650×2,560×750 (143×101×30)	4,920×3,110×925 (194×122×36)
淨重約 Approx. net weight	kg (lb)	8,500 (18,700)	15,000 (33,000)
T型槽 T-slot	Pitch × number	185×9	200×9

### 標準附件

1. 底座滑軌護蓋
2. 安裝零件
3. 液壓力組
4. 拆/裝工具

### Standard accessories

1. Telescopic steel cover for bed slideways
2. Installation part
3. Hydraulic power unit
4. disassembly / reassembly tools

## 自動工具交換 Automatic tool changer (optional accessory)

刀具容量	Tool storage capacity	40/60/90
刀柄	Tool shank	MAS 403 BT-50
拉刀裝置	Pull stud	MAS 403 P50T-1
刀具重量	Tool weight	25kg
刀具最大長度	Max. tool length	350mm
刀具最大直徑	Max. support moment	Φ125mm(Φ250mm)
刀具最大偏載荷重	Tool support moment	80 kg
刀具選擇模式	Tool selection method	Pot address random

