

# 深孔放電加工機

## DRILL EDM



BEST-D2030

BEST-D2535

項目 ITEM	UNIT	BEST-D2030	BEST-D2535	BEST-D3545	BEST-D4055
工作台面積 Work table	mm	460X210	600X300	600X300	800X450
X軸行程 X axis travel	mm	300	350	450	550
Y軸行程 Y axis travel	mm	200	250	350	400
主軸伺服行程 (Z1) Spindle servo travel(Z1)	mm	345			
W軸行程 (Z2) W axis travel(Z2)	mm	NA	200		250
眼模導座行程 (Z3) Electrode guide travel(Z3)	mm	150			
加工液容量 Working fluid tank capacity	L	20L Pure water			
最大加工工件重量 Max.workpiece weight	KGS	200	400	500	800
機械重量(淨重) Machine weight(ent)	KGS	600	800	1000	1500
輸入電源 Power source	V	220/380/440			
最大消耗電力 Max.power consumption	KVA	4KVA			
最大加工電流 Max.machining current	A	30A			

\*註:由於不斷的研究改進,規格若有變更,恕不另行通知。

### 標準配備: STANDARD ACCESSORIES

濾網	Filter	.....	1pc
工具箱	Tool box & kits	.....	1pc
電極眼模	Ceramic guide $\Phi$ 1.0mm	.....	1pc
電極夾頭	Electrode chuck $\Phi$ 0.3-3mm	.....	1pc
電極銅管	Tubing $\Phi$ 1.0mm	.....	10psc
石英燈	Halogen lamp	.....	1pc
XY軸光學尺	XY axes linear scale	.....	1pc
平行墊塊	.....	.....	1pc

### 特殊附件: OPTIONAL ACCESSORIES

電極眼模	Ceramic guide $\Phi$ 0.1-6mm
電極夾頭	Electrode Chuck
電極銅管	Tubing $\Phi$ 0.3-3.0, 0-1.5, 3-6.5mm



**林寶機械貿易私人有限公司**  
**LIM POH MACHINERY TRADING PTE LTD**  
 NO. 111, UBI AVE 4, CIVIC TERRACE WAREHOUSE, SINGAPORE 408761.  
 E-mail: enquiry@limph.com Website: http://www.limph.com  
 TEL: 6846 1138 FAX: 6841 2832  
 GST Reg.No. M2-0067612-5 Business Reg.No. 199404054E