

LC-185VS-B



VS HEAD



TM HEAD



20VS HEAD



20VN HEAD



2G HEAD

►MILLING HEAD SPECIFICATION

Milling Head	VS	TM	20 VS	20 VN	2G	
Spindle Taper	R8 or NST 30	R8 or NST 30	NST 40	NST 40	NST 40	
Spindle Motor(3Ph)	2 HP	2 HP	3 HP	3 HP	5 HP	
Quill Diameter	85.7 mm	85.7 mm	90 mm	90 mm	110 mm	
Quill Travel	127 mm (5")	127 mm (5")	127 mm (5")	127 mm (5")	135 mm (5.3")	
Vertical Feeds	0.04/0.08/0.16 mm	0.04/0.08/0.16 mm	0.04/0.08/0.16 mm	0.04/0.08/0.16 mm	0.035/0.070/0.14 mm	
Spindle Speed	50 HZ	50~3,750 rpm (Variable)	60~2,280 rpm (8 Steps)	50~3,750 rpm (Variable)	60~3,000 rpm (16 Steps)	60~3,000 rpm (16 Steps)
	60 HZ	60~4,500 rpm (Variable)	80~2,760 rpm (8 Steps)	60~4,500 rpm (Variable)	75~3,600 rpm (16 Steps)	75~3,600 rpm (16 Steps)
Inverter (Option)	0	X	X	0	0	
Bigger spindle motor (Option)	3 HP	3 HP	5 HP	5 HP	X	
Single phase motor (Option)	0	0	X	X	X	
2 speed motor (Option)	X	0	X	V	V	

V: Standard ; 0: Option ; X: Not Available